



110V LED RECESSED LIGHTING



1

Built-in protection for unlimited hipoting

2

Shortened profile for low clearance installation

3

Compatibility with most popular industry dimmer switches

4

Protection from back feed flickering

5

High CRI value for true color rendering

6

Easy installation spring clips and consolidated junction box

7

Improved beam spread for better light dispersion



110V LED RECESSED LIGHTING



4" Recessed



6" Recessed

Model	410LS2214	410LS221435K	410LS2216	410LS221635K
Height	2.83 inches	2.83 inches	2.6 inches	2.6 inches
Width	5.35 inches	5.35 inches	7.7 inches	7.7 inches
Rough Opening	4.5 inches	4.5 inches	5.75 inches	5.75 inches
Finish	White	White	White	White
Voltage	120V AC	120V AC	120V AC	120V AC
Frequency	60Hz	60Hz	60Hz	60Hz
Power	9W	9W	15W	15W
Dimmable	Yes	Yes	Yes	Yes
CRI	>90	>90	>90	>90
Lumens	650 lms	650 lms	1050 lms	1050 lms
Color	3000	3500	3000	3500
Luminous Flux	>65	>65	>65	>65
Beam Angle	93°	93°	95.6°	95.6°
Life Time	50,000 hours	50,000 hours	50,000 hours	50,000 hours



Ratings

- IC
- Air Tight
- Wet Location